

# WEST Search History

DATE: Tuesday, November 05, 2002

## Set Name Query

side by side

## Hit Count Set Name

result set

*DB=USPT,PGPB; PLUR=YES; OP=ADJ*

L34	(program\$ with micro near2 device).ab.	11	L34
L33	l3 and l32	0	L33
L32	l30 and l31	240	L32
L31	compar\$ with data	155479	L31
L30	l28 and l29	374	L30
L29	(buffer or register) with data	134167	L29
L28	verif\$ near2 data with programm\$4	531	L28
L27	l3 and l26	0	L27
L26	l24 and l25	29	L26
L25	compar\$ with data with register	11106	L25
L24	l22 and l23	106	L24
L23	socket with (buffer or register)	1523	L23
L22	programm\$5 near3 device	33535	L22
L21	l3 and l20	0	L21
L20	l15 and l19	12	L20
L19	l4 and l18	264	L19
L18	read\$4 near3 programmable near2 device	976	L18
L17	l3 and l16	0	L17
L16	l14 and l15	16	L16
L15	control with enable with device with data	2757	L15
L14	l4 and l13	406	L14
L13	programm\$ near3 programmable near2 device	1831	L13
L12	l10 and l11	0	L12
L11	((digital near2 analog near2 converter) or dac) with (amplifier) same (translat\$4 near2 buffer)	1	L11
L10	buffer same voltage same socket	91	L10
L9	(relay with socket) same (buffer with voltage)	0	L9
L8	pin driver with logic with voltage	21	L8
L7	l4 and l6	1	L7
L6	backplane with socket with voltage	6	L6
L5	pin driver with backplane with voltage	0	L5
L4	address same data same control	81564	L4
L3	l1 or l2	2950	L3
L2	((710/52  710/62  710/72 )!.CCLS. )	1565	L2

L2 ((710/52 |710/62 |710/72 )!.CCLS. )

1565 L2

L1 ((700/90 |700/95 |700/117 |700/121 )!.CCLS. )

1385 L1

END OF SEARCH HISTORY